

DECLARATION OF PERFORMANCE
355-W0-816 REV. 1.7

1. **Steel plate (Quality and type) : S355J0W tk 8 ≤ 16mm;**
Unique identification code of the product-type: 355 W0 816;
2. Intended uses: in metal structures or in composite metal and concrete structures;
3. Manufacturer: OFFICINE TECNOSIDER SRL via del Ledra 31, 33100, Udine; in the plant sited in San Giorgio di Nogaro Via Jacopo Linussio 1 (Z.I. Ausa Corno);
4. Not applicable;
5. System of attestation of conformity of hot rolled structural steel products: 2+;
6. Harmonized standard: EN 10025-1:2004 annex ZA
Notified body: RINA Services S.p.a. Via Corsica, 12 16128 Genova-Italy (notified organization by Directive 89/106/CEE) Identification number: **0474**, certificate **CPR-0538** first issue 27-07-11;
- 6b. Not applicable;
7. Declared performances:

Essential characteristics	Requirement clauses (Always reported on product labelling)	Standard reference
Tolerances on shape and dimension	7.7.1 comply to order requirements	EN 10025-1:2004 EN 10025-5:2004
Elongation	7.3.1 ≥ 20 %	EN 10025-1:2004 EN 10025-5:2004
Tensile strength	7.3.1 470 ÷ 630 MPa	EN 10025-1:2004 EN 10025-5:2004
Yield strength	7.3.1 ≥ 355 MPa	EN 10025-1:2004 EN 10025-5:2004
Impact strength	7.3.1+7.3.2 ≥ 27 J	EN 10025-1:2004 EN 10025-5:2004
Weldability (chemical composition)	7.2+7.4.1 NPd	EN 10025-1:2004 EN 10025-5:2004
Durability (chemical composition)	7.2+7.4.3 NPd	EN 10025-1:2004 EN 10025-5:2004

8. Not applicable;

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

San Giorgio di Nogaro, 12/11/2019

Signed for and on behalf of the
manufacturer by:

CEO - Pinto Giorgio



DECLARATION OF PERFORMANCE
355-W0-1640 REV. 1.7

1. **Steel plate (Quality and type) : S355J0W tk > 16 ≤ 40mm;**
Unique identification code of the product-type: 355 W0 1640;
2. Intended uses: in metal structures or in composite metal and concrete structures;
3. Manufacturer: OFFICINE TECNOSIDER SRL via del Ledra 31, 33100, Udine; in the plant sited in San Giorgio di Nogaro Via Jacopo Linussio 1 (Z.I. Ausa Corno);
4. Not applicable;
5. System of attestation of conformity of hot rolled structural steel products: 2+;
6. Harmonized standard: EN 10025-1:2004 annex ZA
Notified body: RINA Services S.p.a. Via Corsica, 12 16128 Genova-Italy (notified organization by Directive 89/106/CEE) Identification number: **0474**, certificate **CPR-0538** first issue 27-07-11;
- 6b. Not applicable;
7. Declared performances:

Essential characteristics	Requirement clauses (Always reported on product labelling)	Standard reference
Tolerances on shape and dimension	7.7.1 comply to order requirements	EN 10025-1:2004 EN 10025-5:2004
Elongation	7.3.1 ≥ 20 %	EN 10025-1:2004 EN 10025-5:2004
Tensile strength	7.3.1 470 ÷ 630 MPa	EN 10025-1:2004 EN 10025-5:2004
Yield strength	7.3.1 ≥ 345 MPa	EN 10025-1:2004 EN 10025-5:2004
Impact strength	7.3.1+7.3.2 ≥ 27 J	EN 10025-1:2004 EN 10025-5:2004
Weldability (chemical composition)	7.2+7.4.1 NPD	EN 10025-1:2004 EN 10025-5:2004
Durability (chemical composition)	7.2+7.4.3 NPD	EN 10025-1:2004 EN 10025-5:2004

8. Not applicable;

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

San Giorgio di Nogaro, 12/11/2019

Signed for and on behalf of the
manufacturer by:

CEO - Pinto Giorgio



DECLARATION OF PERFORMANCE
355-W0-4063 REV. 1.7

1. **Steel plate (Quality and type) : S355J0W tk > 40 ≤ 63mm;**
Unique identification code of the product-type: 355 W0 4063;
2. Intended uses: in metal structures or in composite metal and concrete structures;
3. Manufacturer: OFFICINE TECNOSIDER SRL via del Ledra 31, 33100, Udine; in the plant sited in San Giorgio di Nogaro Via Jacopo Linussio 1 (Z.I. Aussa Corno);
4. Not applicable;
5. System of attestation of conformity of hot rolled structural steel products: 2+;
6. Harmonized standard: EN 10025-1:2004 annex ZA
Notified body: RINA Services S.p.a. Via Corsica, 12 16128 Genova-Italy (notified organization by Directive 89/106/CEE) Identification number: **0474**, certificate **CPR-0538** first issue 27-07-11;
- 6b. Not applicable;
7. Declared performances:

Essential characteristics	Requirement clauses (Always reported on product labelling)	Standard reference
Tolerances on shape and dimension	7.7.1 comply to order requirements	EN 10025-1:2004 EN 10025-5:2004
Elongation	7.3.1 ≥ 19 %	EN 10025-1:2004 EN 10025-5:2004
Tensile strength	7.3.1 470 ÷ 630 MPa	EN 10025-1:2004 EN 10025-5:2004
Yield strength	7.3.1 ≥ 335 MPa	EN 10025-1:2004 EN 10025-5:2004
Impact strength	7.3.1+7.3.2 ≥ 27 J	EN 10025-1:2004 EN 10025-5:2004
Weldability (chemical composition)	7.2+7.4.1 NPD	EN 10025-1:2004 EN 10025-5:2004
Durability (chemical composition)	7.2+7.4.3 NPD	EN 10025-1:2004 EN 10025-5:2004

8. Not applicable;

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

San Giorgio di Nogaro, 12/11/2019

Signed for and on behalf of the
manufacturer by:

CEO - Pinto Giorgio



DECLARATION OF PERFORMANCE
355-W0-6380 REV. 1.7

1. **Steel plate (Quality and type) : S355J0W tk > 63 ≤ 80mm;**
Unique identification code of the product-type: 355 W0 6380;
2. Intended uses: in metal structures or in composite metal and concrete structures;
3. Manufacturer: OFFICINE TECNOSIDER SRL via del Ledra 31, 33100, Udine; in the plant sited in San Giorgio di Nogaro Via Jacopo Linussio 1 (Z.I. Ausa Corno);
4. Not applicable;
5. System of attestation of conformity of hot rolled structural steel products: 2+;
6. Harmonized standard: EN 10025-1:2004 annex ZA
Notified body: RINA Services S.p.a. Via Corsica, 12 16128 Genova-Italy (notified organization by Directive 89/106/CEE) Identification number: **0474**, certificate **CPR-0538** first issue 27-07-11;
- 6b. Not applicable;
7. Declared performances:

Essential characteristics	Requirement clauses (Always reported on product labelling)	Standard reference
Tolerances on shape and dimension	7.7.1 comply to order requirements	EN 10025-1:2004 EN 10025-5:2004
Elongation	7.3.1 ≥ 18 %	EN 10025-1:2004 EN 10025-5:2004
Tensile strength	7.3.1 470 ÷ 630 MPa	EN 10025-1:2004 EN 10025-5:2004
Yield strength	7.3.1 ≥ 325 MPa	EN 10025-1:2004 EN 10025-5:2004
Impact strength	7.3.1+7.3.2 ≥ 27 J	EN 10025-1:2004 EN 10025-5:2004
Weldability (chemical composition)	7.2+7.4.1 NPD	EN 10025-1:2004 EN 10025-5:2004
Durability (chemical composition)	7.2+7.4.3 NPD	EN 10025-1:2004 EN 10025-5:2004

8. Not applicable;

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

San Giorgio di Nogaro, 12/11/2019

Signed for and on behalf of the
manufacturer by:

CEO - Pinto Giorgio



DECLARATION OF PERFORMANCE
355-W0-80100 REV. 1.7

1. **Steel plate (Quality and type) : S355J0W tk > 80 ≤ 100mm;**
Unique identification code of the product-type: 355 W0 80100;
2. Intended uses: in metal structures or in composite metal and concrete structures;
3. Manufacturer: OFFICINE TECNOSIDER SRL via del Ledra 31, 33100, Udine; in the plant sited in San Giorgio di Nogaro Via Jacopo Linussio 1 (Z.I. Aussa Corno);
4. Not applicable;
5. System of attestation of conformity of hot rolled structural steel products: 2+;
6. Harmonized standard: EN 10025-1:2004 annex ZA
Notified body: RINA Services S.p.a. Via Corsica, 12 16128 Genova-Italy (notified organization by Directive 89/106/CEE) Identification number: **0474**, certificate **CPR-0538** first issue 27-07-11;
- 6b. Not applicable;
7. Declared performances:

Essential characteristics	Requirement clauses (Always reported on product labelling)	Standard reference
Tolerances on shape and dimension	7.7.1 comply to order requirements	EN 10025-1:2004 EN 10025-5:2004
Elongation	7.3.1 ≥ 18 %	EN 10025-1:2004 EN 10025-5:2004
Tensile strength	7.3.1 470 ÷ 630 MPa	EN 10025-1:2004 EN 10025-5:2004
Yield strength	7.3.1 ≥ 315 MPa	EN 10025-1:2004 EN 10025-5:2004
Impact strength	7.3.1+7.3.2 ≥ 27 J	EN 10025-1:2004 EN 10025-5:2004
Weldability (chemical composition)	7.2+7.4.1 NPD	EN 10025-1:2004 EN 10025-5:2004
Durability (chemical composition)	7.2+7.4.3 NPD	EN 10025-1:2004 EN 10025-5:2004

8. Not applicable;

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

San Giorgio di Nogaro, 12/11/2019

Signed for and on behalf of the
manufacturer by:

CEO - Pinto Giorgio



DECLARATION OF PERFORMANCE
355-W2-816 REV. 1.7

1. **Steel plate (Quality and type) : S355J2W tk 8 ≤ 16mm;**
Unique identification code of the product-type: 355 W2 816;
2. Intended uses: in metal structures or in composite metal and concrete structures;
3. Manufacturer: OFFICINE TECNOSIDER SRL via del Ledra 31, 33100, Udine; in the plant sited in San Giorgio di Nogaro Via Jacopo Linussio 1 (Z.I. Aussa Corno);
4. Not applicable;
5. System of attestation of conformity of hot rolled structural steel products: 2+;
6. Harmonized standard: EN 10025-1:2004 annex ZA
Notified body: RINA Services S.p.a. Via Corsica, 12 16128 Genova-Italy (notified organization by Directive 89/106/CEE) Identification number: **0474**, certificate **CPR-0538** first issue 27-07-11;
- 6b. Not applicable;
7. Declared performances:

Essential characteristics	Requirement clauses (Always reported on product labelling)	Standard reference
Tolerances on shape and dimension	7.7.1 comply to order requirements	EN 10025-1:2004 EN 10025-5:2004
Elongation	7.3.1 ≥ 20 %	EN 10025-1:2004 EN 10025-5:2004
Tensile strength	7.3.1 470 ÷ 630 MPa	EN 10025-1:2004 EN 10025-5:2004
Yield strength	7.3.1 ≥ 355 MPa	EN 10025-1:2004 EN 10025-5:2004
Impact strength	7.3.1+7.3.2 ≥ 27 J	EN 10025-1:2004 EN 10025-5:2004
Weldability (chemical composition)	7.2+7.4.1 NPD	EN 10025-1:2004 EN 10025-5:2004
Durability (chemical composition)	7.2+7.4.3 NPD	EN 10025-1:2004 EN 10025-5:2004

8. Not applicable;

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

San Giorgio di Nogaro, 12/11/2019

Signed for and on behalf of the
manufacturer by:

CEO - Pinto Giorgio



DECLARATION OF PERFORMANCE
355-W2-1640 REV. 1.7

1. **Steel plate (Quality and type) : S355J2W tk > 16 ≤ 40mm;**
Unique identification code of the product-type: 355 W2 1640;
2. Intended uses: in metal structures or in composite metal and concrete structures;
3. Manufacturer: OFFICINE TECNOSIDER SRL via del Ledra 31, 33100, Udine; in the plant sited in San Giorgio di Nogaro Via Jacopo Linussio 1 (Z.I. Ausa Corno);
4. Not applicable;
5. System of attestation of conformity of hot rolled structural steel products: 2+;
6. Harmonized standard: EN 10025-1:2004 annex ZA
Notified body: RINA Services S.p.a. Via Corsica, 12 16128 Genova-Italy (notified organization by Directive 89/106/CEE) Identification number: **0474**, certificate **CPR-0538** first issue 27-07-11;
- 6b. Not applicable;
7. Declared performances:

Essential characteristics	Requirement clauses (Always reported on product labelling)	Standard reference
Tolerances on shape and dimension	7.7.1 comply to order requirements	EN 10025-1:2004 EN 10025-5:2004
Elongation	7.3.1 ≥ 20 %	EN 10025-1:2004 EN 10025-5:2004
Tensile strength	7.3.1 470 ÷ 630 MPa	EN 10025-1:2004 EN 10025-5:2004
Yield strength	7.3.1 ≥ 345 MPa	EN 10025-1:2004 EN 10025-5:2004
Impact strength	7.3.1+7.3.2 ≥ 27 J	EN 10025-1:2004 EN 10025-5:2004
Weldability (chemical composition)	7.2+7.4.1 NPD	EN 10025-1:2004 EN 10025-5:2004
Durability (chemical composition)	7.2+7.4.3 NPD	EN 10025-1:2004 EN 10025-5:2004

8. Not applicable;

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

San Giorgio di Nogaro, 12/11/2019

Signed for and on behalf of the
manufacturer by:

CEO - Pinto Giorgio



DECLARATION OF PERFORMANCE
355-W2-4063 REV. 1.7

1. **Steel plate (Quality and type) : S355J2W tk > 40 ≤ 63mm;**
Unique identification code of the product-type: 355 W2 4063;
2. Intended uses: in metal structures or in composite metal and concrete structures;
3. Manufacturer: OFFICINE TECNOSIDER SRL via del Ledra 31, 33100, Udine; in the plant sited in San Giorgio di Nogaro Via Jacopo Linussio 1 (Z.I. Ausa Corno);
4. Not applicable;
5. System of attestation of conformity of hot rolled structural steel products: 2+;
6. Harmonized standard: EN 10025-1:2004 annex ZA
Notified body: RINA Services S.p.a. Via Corsica, 12 16128 Genova-Italy (notified organization by Directive 89/106/CEE) Identification number: **0474**, certificate **CPR-0538** first issue 27-07-11;
- 6b. Not applicable;
7. Declared performances:

Essential characteristics	Requirement clauses (Always reported on product labelling)	Standard reference
Tolerances on shape and dimension	7.7.1 comply to order requirements	EN 10025-1:2004 EN 10025-5:2004
Elongation	7.3.1 ≥ 19 %	EN 10025-1:2004 EN 10025-5:2004
Tensile strength	7.3.1 470 ÷ 630 MPa	EN 10025-1:2004 EN 10025-5:2004
Yield strength	7.3.1 ≥ 335 MPa	EN 10025-1:2004 EN 10025-5:2004
Impact strength	7.3.1+7.3.2 ≥ 27 J	EN 10025-1:2004 EN 10025-5:2004
Weldability (chemical composition)	7.2+7.4.1 NPD	EN 10025-1:2004 EN 10025-5:2004
Durability (chemical composition)	7.2+7.4.3 NPD	EN 10025-1:2004 EN 10025-5:2004

8. Not applicable;

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

San Giorgio di Nogaro, 12/11/2019

Signed for and on behalf of the
manufacturer by:

CEO - Pinto Giorgio



DECLARATION OF PERFORMANCE
355-W2-6380 REV. 1.7

1. **Steel plate (Quality and type) : S355J2W tk > 63 ≤ 80mm;**
Unique identification code of the product-type: 355 W2 6380;
2. Intended uses: in metal structures or in composite metal and concrete structures;
3. Manufacturer: OFFICINE TECNOSIDER SRL via del Ledra 31, 33100, Udine; in the plant sited in San Giorgio di Nogaro Via Jacopo Linussio 1 (Z.I. Aussa Corno);
4. Not applicable;
5. System of attestation of conformity of hot rolled structural steel products: 2+;
6. Harmonized standard: EN 10025-1:2004 annex ZA
Notified body: RINA Services S.p.a. Via Corsica, 12 16128 Genova-Italy (notified organization by Directive 89/106/CEE) Identification number: **0474**, certificate **CPR-0538** first issue 27-07-11;
- 6b. Not applicable;
7. Declared performances:

Essential characteristics	Requirement clauses (Always reported on product labelling)	Standard reference
Tolerances on shape and dimension	7.7.1 comply to order requirements	EN 10025-1:2004 EN 10025-5:2004
Elongation	7.3.1 ≥ 18 %	EN 10025-1:2004 EN 10025-5:2004
Tensile strength	7.3.1 470 ÷ 630 MPa	EN 10025-1:2004 EN 10025-5:2004
Yield strength	7.3.1 ≥ 325 MPa	EN 10025-1:2004 EN 10025-5:2004
Impact strength	7.3.1+7.3.2 ≥ 27 J	EN 10025-1:2004 EN 10025-5:2004
Weldability (chemical composition)	7.2+7.4.1 NPD	EN 10025-1:2004 EN 10025-5:2004
Durability (chemical composition)	7.2+7.4.3 NPD	EN 10025-1:2004 EN 10025-5:2004

8. Not applicable;

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

San Giorgio di Nogaro, 12/11/2019

Signed for and on behalf of the
manufacturer by:

CEO - Pinto Giorgio



DECLARATION OF PERFORMANCE
355-W2-80100 REV. 1.7

1. **Steel plate (Quality and type) : S355J2W tk > 80 ≤ 100mm;**
Unique identification code of the product-type: 355 W2 80100;
2. Intended uses: in metal structures or in composite metal and concrete structures;
3. Manufacturer: OFFICINE TECNOSIDER SRL via del Ledra 31, 33100, Udine; in the plant sited in San Giorgio di Nogaro Via Jacopo Linussio 1 (Z.I. Aussa Corno);
4. Not applicable;
5. System of attestation of conformity of hot rolled structural steel products: 2+;
6. Harmonized standard: EN 10025-1:2004 annex ZA
Notified body: RINA Services S.p.a. Via Corsica, 12 16128 Genova-Italy (notified organization by Directive 89/106/CEE) Identification number: **0474**, certificate **CPR-0538** first issue 27-07-11;
- 6b. Not applicable;
7. Declared performances:

Essential characteristics	Requirement clauses (Always reported on product labelling)	Standard reference
Tolerances on shape and dimension	7.7.1 comply to order requirements	EN 10025-1:2004 EN 10025-5:2004
Elongation	7.3.1 ≥ 18 %	EN 10025-1:2004 EN 10025-5:2004
Tensile strength	7.3.1 470 ÷ 630 MPa	EN 10025-1:2004 EN 10025-5:2004
Yield strength	7.3.1 ≥ 315 MPa	EN 10025-1:2004 EN 10025-5:2004
Impact strength	7.3.1+7.3.2 ≥ 27 J	EN 10025-1:2004 EN 10025-5:2004
Weldability (chemical composition)	7.2+7.4.1 NPD	EN 10025-1:2004 EN 10025-5:2004
Durability (chemical composition)	7.2+7.4.3 NPD	EN 10025-1:2004 EN 10025-5:2004

8. Not applicable;

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

San Giorgio di Nogaro, 12/11/2019

Signed for and on behalf of the
manufacturer by:

CEO - Pinto Giorgio



DECLARATION OF PERFORMANCE
355-KW-816 REV. 1.7

1. **Steel plate (Quality and type) : S355K2W tk 8 ≤ 16mm;**
Unique identification code of the product-type: 355 KW 816;
2. Intended uses: in metal structures or in composite metal and concrete structures;
3. Manufacturer: OFFICINE TECNOSIDER SRL via del Ledra 31, 33100, Udine; in the plant sited in San Giorgio di Nogaro Via Jacopo Linussio 1 (Z.I. Aussa Corno);
4. Not applicable;
5. System of attestation of conformity of hot rolled structural steel products: 2+;
6. Harmonized standard: EN 10025-1:2004 annex ZA
Notified body: RINA Services S.p.a. Via Corsica, 12 16128 Genova-Italy (notified organization by Directive 89/106/CEE) Identification number: **0474**, certificate **CPR-0538** first issue 27-07-11;
- 6b. Not applicable;
7. Declared performances:

Essential characteristics	Requirement clauses (Always reported on product labelling)	Standard reference
Tolerances on shape and dimension	7.7.1 comply to order requirements	EN 10025-1:2004 EN 10025-5:2004
Elongation	7.3.1 ≥ 20 %	EN 10025-1:2004 EN 10025-5:2004
Tensile strength	7.3.1 470 ÷ 630 MPa	EN 10025-1:2004 EN 10025-5:2004
Yield strength	7.3.1 ≥ 355 MPa	EN 10025-1:2004 EN 10025-5:2004
Impact strength	7.3.1+7.3.2 ≥ 40 J	EN 10025-1:2004 EN 10025-5:2004
Weldability (chemical composition)	7.2+7.4.1 NPD	EN 10025-1:2004 EN 10025-5:2004
Durability (chemical composition)	7.2+7.4.3 NPD	EN 10025-1:2004 EN 10025-5:2004

8. Not applicable;

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

San Giorgio di Nogaro, 12/11/2019

Signed for and on behalf of the
manufacturer by:

CEO - Pinto Giorgio



DECLARATION OF PERFORMANCE
355-KW-1640 REV. 1.7

1. **Steel plate (Quality and type) : S355K2W tk > 16 ≤ 40mm;**
Unique identification code of the product-type: 355 KW 1640;
2. Intended uses: in metal structures or in composite metal and concrete structures;
3. Manufacturer: OFFICINE TECNOSIDER SRL via del Ledra 31, 33100, Udine; in the plant sited in San Giorgio di Nogaro Via Jacopo Linussio 1 (Z.I. Ausa Corno);
4. Not applicable;
5. System of attestation of conformity of hot rolled structural steel products: 2+;
6. Harmonized standard: EN 10025-1:2004 annex ZA
Notified body: RINA Services S.p.a. Via Corsica, 12 16128 Genova-Italy (notified organization by Directive 89/106/CEE) Identification number: **0474**, certificate **CPR-0538** first issue 27-07-11;
- 6b. Not applicable;
7. Declared performances:

Essential characteristics	Requirement clauses (Always reported on product labelling)	Standard reference
Tolerances on shape and dimension	7.7.1 comply to order requirements	EN 10025-1:2004 EN 10025-5:2004
Elongation	7.3.1 ≥ 20 %	EN 10025-1:2004 EN 10025-5:2004
Tensile strength	7.3.1 470 ÷ 630 MPa	EN 10025-1:2004 EN 10025-5:2004
Yield strength	7.3.1 ≥ 345 MPa	EN 10025-1:2004 EN 10025-5:2004
Impact strength	7.3.1+7.3.2 ≥ 40 J	EN 10025-1:2004 EN 10025-5:2004
Weldability (chemical composition)	7.2+7.4.1 NPD	EN 10025-1:2004 EN 10025-5:2004
Durability (chemical composition)	7.2+7.4.3 NPD	EN 10025-1:2004 EN 10025-5:2004

8. Not applicable;

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

San Giorgio di Nogaro, 12/11/2019

Signed for and on behalf of the
manufacturer by:

CEO - Pinto Giorgio



DECLARATION OF PERFORMANCE
355-KW-4063 REV. 1.7

1. **Steel plate (Quality and type) : S355K2W tk > 40 ≤ 63mm;**
Unique identification code of the product-type: 355 KW 4063;
2. Intended uses: in metal structures or in composite metal and concrete structures;
3. Manufacturer: OFFICINE TECNOSIDER SRL via del Ledra 31, 33100, Udine; in the plant sited in San Giorgio di Nogaro Via Jacopo Linussio 1 (Z.I. Aussa Corno);
4. Not applicable;
5. System of attestation of conformity of hot rolled structural steel products: 2+;
6. Harmonized standard: EN 10025-1:2004 annex ZA
Notified body: RINA Services S.p.a. Via Corsica, 12 16128 Genova-Italy (notified organization by Directive 89/106/CEE) Identification number: **0474**, certificate **CPR-0538** first issue 27-07-11;
- 6b. Not applicable;
7. Declared performances:

Essential characteristics	Requirement clauses (Always reported on product labelling)	Standard reference
Tolerances on shape and dimension	7.7.1 comply to order requirements	EN 10025-1:2004 EN 10025-5:2004
Elongation	7.3.1 ≥ 19 %	EN 10025-1:2004 EN 10025-5:2004
Tensile strength	7.3.1 470 ÷ 630 MPa	EN 10025-1:2004 EN 10025-5:2004
Yield strength	7.3.1 ≥ 335 MPa	EN 10025-1:2004 EN 10025-5:2004
Impact strength	7.3.1+7.3.2 ≥ 40 J	EN 10025-1:2004 EN 10025-5:2004
Weldability (chemical composition)	7.2+7.4.1 NPD	EN 10025-1:2004 EN 10025-5:2004
Durability (chemical composition)	7.2+7.4.3 NPD	EN 10025-1:2004 EN 10025-5:2004

8. Not applicable;

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

San Giorgio di Nogaro, 12/11/2019

Signed for and on behalf of the
manufacturer by:

CEO - Pinto Giorgio



DECLARATION OF PERFORMANCE
355-KW-6380 REV. 1.7

1. **Steel plate (Quality and type) : S355K2W tk > 63 ≤ 80mm;**
Unique identification code of the product-type: 355 KW 6380;
2. Intended uses: in metal structures or in composite metal and concrete structures;
3. Manufacturer: OFFICINE TECNOSIDER SRL via del Ledra 31, 33100, Udine; in the plant sited in San Giorgio di Nogaro Via Jacopo Linussio 1 (Z.I. Ausa Corno);
4. Not applicable;
5. System of attestation of conformity of hot rolled structural steel products: 2+;
6. Harmonized standard: EN 10025-1:2004 annex ZA
Notified body: RINA Services S.p.a. Via Corsica, 12 16128 Genova-Italy (notified organization by Directive 89/106/CEE) Identification number: **0474**, certificate **CPR-0538** first issue 27-07-11;
- 6b. Not applicable;
7. Declared performances:

Essential characteristics	Requirement clauses (Always reported on product labelling)	Standard reference
Tolerances on shape and dimension	7.7.1 comply to order requirements	EN 10025-1:2004 EN 10025-5:2004
Elongation	7.3.1 ≥ 18 %	EN 10025-1:2004 EN 10025-5:2004
Tensile strength	7.3.1 470 ÷ 630 MPa	EN 10025-1:2004 EN 10025-5:2004
Yield strength	7.3.1 ≥ 325 MPa	EN 10025-1:2004 EN 10025-5:2004
Impact strength	7.3.1+7.3.2 ≥ 40 J	EN 10025-1:2004 EN 10025-5:2004
Weldability (chemical composition)	7.2+7.4.1 NPD	EN 10025-1:2004 EN 10025-5:2004
Durability (chemical composition)	7.2+7.4.3 NPD	EN 10025-1:2004 EN 10025-5:2004

8. Not applicable;

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

San Giorgio di Nogaro, 12/11/2019

Signed for and on behalf of the
manufacturer by:

CEO - Pinto Giorgio



DECLARATION OF PERFORMANCE
355-KW-80100 REV. 1.7

1. **Steel plate (Quality and type) : S355K2W tk > 80 ≤ 100mm;**
Unique identification code of the product-type: 355 KW 80100;
2. Intended uses: in metal structures or in composite metal and concrete structures;
3. Manufacturer: OFFICINE TECNOSIDER SRL via del Ledra 31, 33100, Udine; in the plant sited in San Giorgio di Nogaro Via Jacopo Linussio 1 (Z.I. Aussa Corno);
4. Not applicable;
5. System of attestation of conformity of hot rolled structural steel products: 2+;
6. Harmonized standard: EN 10025-1:2004 annex ZA
Notified body: RINA Services S.p.a. Via Corsica, 12 16128 Genova-Italy (notified organization by Directive 89/106/CEE) Identification number: **0474**, certificate **CPR-0538** first issue 27-07-11;
- 6b. Not applicable;
7. Declared performances:

Essential characteristics	Requirement clauses (Always reported on product labelling)	Standard reference
Tolerances on shape and dimension	7.7.1 comply to order requirements	EN 10025-1:2004 EN 10025-5:2004
Elongation	7.3.1 ≥ 18 %	EN 10025-1:2004 EN 10025-5:2004
Tensile strength	7.3.1 470 ÷ 630 MPa	EN 10025-1:2004 EN 10025-5:2004
Yield strength	7.3.1 ≥ 315 MPa	EN 10025-1:2004 EN 10025-5:2004
Impact strength	7.3.1+7.3.2 ≥ 40 J	EN 10025-1:2004 EN 10025-5:2004
Weldability (chemical composition)	7.2+7.4.1 NPD	EN 10025-1:2004 EN 10025-5:2004
Durability (chemical composition)	7.2+7.4.3 NPD	EN 10025-1:2004 EN 10025-5:2004

8. Not applicable;

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

San Giorgio di Nogaro, 12/11/2019

Signed for and on behalf of the
manufacturer by:

CEO - Pinto Giorgio

